

CANYON STRIVE CFR 2020
SPECIFICATIONS & GEOMETRIES

SPECIFICATIONS STRIVE CFR

	STRIVE CFR 9.0	STRIVE CFR 9.0 LTD
FRAME	Canyon Strive CFR	Canyon Strive CFR
FORK	FOX 36 Factory Grip2 170 mm	RockShox Lyrik Ultimate 170 mm
REAR SHOCK	FOX DPX2 Factory 150 mm	RockShox Super Deluxe Ultimate 150 mm w/ QUARQ Shockwiz
GROUPSET	Shimano XTR	SRAM XX1 Eagle AXS
BRAKES	Shimano XTR	SRAM Code RSC
WHEELS	DT Swiss EXC1200, 29 inch	ZIPP Moto w/ QUARQ Tyrewiz, 29 inch
RIM WIDTH	30 mm	30 mm
TYRES	Maxxis Minion DHR 2.4 Front: MaxxGrip, Back: MaxxTerra	Maxxis Minion DHR 2.4 Front: MaxxGrip, Back: MaxxTerra
CRANK	Race Face Next SL	SRAM XX/X0
RATIO	32 10-51	32 10-50
STEM	G5	G5
HANDLEBAR	G5 CF	G5 CF
SADDLE	SDG Radar	SDG Radar
SEAT POST	FOX Transfer Performance Elite	RockShox Reverb AXS
COLOURS	Minimal, Team	Team
FRAME SIZES	S, M, L, XL	S, M, L, XL
WEIGHT (TUBELESS)	13.3 kg	14.2 kg
PRICE	5,999 €	9,000 €

GEOMETRIES STRIVE CFR

FRAME SIZE	S	M	L	XL
RECOMMENDED RIDER HEIGHT	158-168	168-178	178-188	188-200
SEAT TUBE LENGTH (mm)	400	440	455	500
TOP TUBE LENGTH (horizontal, mm)	602	629	662	697
HEAD TUBE LENGTH (mm)	95	100	110	130
HEAD TUBE ANGLE (°)	65.5-67	65.5-67	65.5-67	65.5-67
SEAT TUBE ANGLE (effective, °)	73.5-75	73.5-75	73.5-75	73.5-75
CHAIN STAY LENGTH (mm)	435	435	435	435
WHEELBASE (mm)	1166	1193	1227	1266
STACK	630	635	644	663
REACH	409	434	464	494
STR	1,54	1,46	1,00	1,34
SPACERS (mm)	20	20	20	20
STEM (mm)	40	40	40	40
HANDLEBAR WIDTH (mm)	780	780	780	780
CRANK ARM LENGTH (mm)	165	165	165	165
SEATPOST DIAMETER (mm)	30.9	30.9	30.9	30.9
SEATPOST LENGTH (mm)	390	440	440	440
WHEEL SIZE	29	29	29	29

ARTWORK



MINIMAL



TEAM

IMPRINT

Canyon Bicycles GmbH
Karl-Tesche-Straße 12
56073 Koblenz
Germany

T +49 (0) 261 9490 3000
info@canyon.com

CANYON.COM