

Exceed CFR Gravel geometry chart

Size		S	M	L	XL
Body height min	[cm]	166	175	183	192
Body height max	[cm]	175	183	192	200
ST length	[mm]	350	415	455	495
BB drop rear	[mm]	75	75	75	75
BB drop front	[mm]	75	75	75	75
BB height	[mm]	292	292	292	292
CS length horizontal	[mm]	425	425	425	430
CS length effective	[mm]	0	429	429	434
HT angle	[°]	68,3	69,3	69,3	69,3
HT length	[mm]	90	95	105	125
Reach	[mm]	432	449	471	489
Stack	[mm]	582	586	595	614
Wheelbase	[mm]	1093	1112	1138	1168
Front Center	[mm]	672	690	716	741
Reach+	[mm]	571	593	615	633
Stack+	[mm]	632	641	650	669
TT length (horizontal)	[mm]	564	581	605	628
Reference fork length	[mm]	466,6	466,6	466,6	466,6
Reference fork offset	[mm]	44	44	44	44
Reference headset stack bottom	[mm]	1	1	1	1
Reference seat height	[mm]	720	720	720	720
Reference wheel diameter front	[mm]	734	734	734	734
Reference wheel diameter rear	[mm]	734	734	734	734
ST angle actual	[°]	76,5	76,5	76,5	76,6
ST angle effective	[°]	77,3	77,3	77,3	77,3
ST offset	[mm]	9	10	10	10
Standover	[mm]	746	771	797	827