

Polaroid Flip Instant Camera

polaroid



Technical Specifications

Product	Polaroid Flip Instant Camera		
Color	PRD	EAN	GTIN
	Black	009152 9120096778155	19120096778152
	White	009151 9120096778148	19120096778145
Launch Date	13/05/2025		
RRP	\$199.99, €219.99, £199.99		
HS or HTS Code	9006409000 (US) 9006400000 (EU)		
Country of Origin	China (CN)		
Packaging Contents	Polaroid Flip Camera Neck Strap Quick Start Guide Safety & Compliance Leaflet		
Product Box	99 x 124 x 178 mm 3,9" x 4,9" x 7"		
Product Box Weight	792 g		
Shipper	380 x 203 x 192 mm 15" x 8" x 7,6"		
Shipper Weight	5.12 kg		
Units per Shipper	6		
Product Dimensions	Lid closed: • 163.5 x 117.2 x 89.7 mm • 6.44" x 4.61" x 3.53" Lid open: • 163.5 x 117.2 x 121.6 mm • 6.44" x 4.61" x 4.79"		
Product Weight	648 grams 22.86 ounces		
Compatible With	i-Type Film 600 Film		
App Enabled	App Enabled Fully control your camera remotely For iOS & Android		

Battery	Lithium-Ion Polymer Soft-Pack Battery. User-serviceable			
Battery Report	Available			
Outer Shell	ABS, PC, PMMA, Mylar PET			
Shutter System	Fastest shutter speed 1/200, exposure time range is 1/200~30s., and Bulb mode (up to 99hrs.)			
Aperture	Maximum f8.5 practical aperture, available apertures: f8.5 - f66.6 (depending on selected zone)			
Lens	Two-lens structure with 4 zones. Auto-switching hyperfocal optical system.			
Field of View	Horizontal: 39.4° Vertical: 40.8°			
Focal Length	Close-up Lens 1	Near Field Lens 2	Mid Field Lens 3	Far Field Lens 4
	94.17 mm	97.75 mm	101.4 mm	106.99 mm
Zone range	0.4 m - 0.77 m	0.77 m - 1.03 m	1.03 m - 1.68 m	1.68 m - infinity
Best focus	.65 m	.85 m	1.2 m	2.5 m
Ranging system	Ultrasonic sensor (0.4 m - 4 m)			
Light meter	40.8° vertical, 39.4° horizontal. Center-weighted single-zone metering (80% coverage of optical FOV)			
Flash System	Vacuum discharge tube strobe range 4.5m @f8 / 14.76' @f8			
Device Interface Ports	USB Type-C charging input x1			
Display	LED display for modes, film count, battery level.			
Other	Bluetooth Viewfinder scene analysis LED warning Tripod mount Built in lens filter snap/click mount			

Distributed by Polaroid International B.V. 1013 AP, Amsterdam, The Netherlands

The POLAROID word and logos are protected trademarks of Polaroid.

Please note that the product is under development. The images in this document are therefore of indicative nature. Please contact your Polaroid sales representative to acquire approved press materials.