

VELOTRIC



VELOTRIC PACKER¹

SIZE
5'3" - 6'6"

Haul it all with our heavy-duty cargo e-bike designed to lighten up your day.



● Sky Blue



● Indigo Gray



Max Range

52 miles

Power

750W(Peak 1200W)

Torque

75Nm

PAS levels

5

Weight

75 lbs

Brakes

Hydraulic Disc Brake 4-Piston with 180mm front and rear

Class 2

20 MPH default-adjustable (Class 1-removable throttle, Class 3-software adjustment)

SPECIFICATIONS

Because It's  Fun.

FRAMESET	Fork	Hydraulic suspension with 80mm travel, 15x110mm thru-axle, with Lock-out
	Frame	Aluminum alloy, fully integrated & lockable down tube battery, internal cable routing, front and rear fenders
	Height Range	5'3" - 6'6"
ELECTRONICS	Motor Hub	750W, Peak 1200W, 75Nm
	Battery	48V, 14.4Ah, 691.2Wh
	Cell	LG 21700
	Charger	48V, 3A, Operates on 100V-240V AC, 50-60Hz (0-80% 4 Hours, 0-100% 6 Hours)
	Display	3.5" Backlit LCD display with speed, trip, battery, assist Level and more
	Security	Apple Find My™
	USB Port	5V 500mA, output for external devices
	Throttle Assist	Thumb-control, removable
	Headlight	12V/5W/130Lux high-output integrated LED, 130lux, Adjustable angle
	Tail Light	Integrated with rear rack, brake highlight
	Pedal Assist	Eco, Tour, Normal, Sport and Turbo pedal assist
	Walk Mode	2.9 MPH
	Water Resistant	IPX6
	SPEED & RANGE	Top Speed
Max Range		Up to 52 Miles
Hill Grade		Throttle only: 10° (18%), Pedal Assist: 12° (21%)
DRIVETRAIN	Chainrings	46T
	Crankset	Aluminum alloy, 170mm
	Cassette	8-speed, 13-34T
	Rear Derailleur	SHIMANO M310-8
	Shift Lever	SHIMANO M315-8
	Chain	KMC Z8.3
BRAKE	Brake	Hydraulic Disc Brake 4-Piston
	Rotors	180mm front and rear
	Brake Levers	Aluminum Alloy, with adjustable reach and power cutoff switch
WHEEL	Rims	Double-wall Aluminum alloy, (F) 26" disc x 36 hole / (R) 20" disc x 36 hole
	Front Hub	NOVATEC Aluminum alloy J-hook disc hub, 15x110mm thru-axle
	Tire	(F) CST 26x2.4" (R) CST 20x3.0" Ebike puncture resistant tires
COCKPIT	Handlebar	6061 Aluminum alloy, Ø31.8mm, 680mm
	Grips	Durable ergonomic grips
	Stem	6061 Aluminum alloy, 3D-forged alloy, angle adjustment 60 degrees, 31.8mm clamp, 90mm length
	Saddle	VELOTRIC urban comfort ergonomic seat
	SeatPost	6061 Aluminum alloy, 30.4 x 350mm, quick release clamp
Storage Bag	Storage bag	Waterproof, TSA lock
SUPPORTS	Fenders	Front and rear full coverage
	Pedals	Plastic
	Kickstand	Aluminum alloy, dual leg, spring loaded, center mount
WEIGHT & LOAD	Bike Weight	75lbs
	Rear rack Load Capacity	176lbs
	Max Bike Load	440lbs